

DIESEL EXHAUST FLUID

FUEL

Air, Electric, Hand Operated Pumps & Meters

Recommended For Pumping DEF (Diesel Exhaust Fluid)



10193

375



11219

369



385

387

Part#	Container	Output
10193	15-55 gallon	1gal. per 13 strokes
375	15-55 gallon	1gal. per 10 strokes
11219	15-55 gallon	1gal. per 24 revolutions
369	15-55 gallon	Siphons 7gal. per min
385	55 gallon	1gal. per 6 lifts
387	15-55 gallon	1gal. per 8 lifts



PART# 1035SP

Air Operated
1:1 Double Diaphragm Pump

- Flow rate 14 GPM
- 1/2" NPT inlet/outlet
- Non-stalling



PART# DEF-005

115-Volt DEF Pump System



Features

- Sealed solution bung adapter w/buttress thread
- 8-ft Goodyear DEF dispensing hose w/ stainless steel clamp
- Stainless steel automatic shutoff nozzle

Part#	Container	Pump length	Output
DEF-005	55 gallon	40"	5 GPM
DEF-010	275 gallon	48"	5 GPM

Optional Accessories: 148 Drum cart & DEF-504 Meter



PART# DEF-504

Nylon Digital Turbine meter

- 1" NPT Inlet/outlet
- Flow rate 3 to 30 GPM
- Powered by 2 AAA Batteries
- 150 PSI